



备注:

1. 塑胶材质: LCP UL 94V-0 BLACK;
2. 毛边最大0.03mm, 厚0.05mm;
3. 产品不可有明显的缩水, 烧焦, 发白, 缺胶, 端子包胶等问题;
4. 零件必须符合RoHS要求;
5. ▼符号为QIP管控尺寸;
6. 模穴号 (A, B, C.....);
7. 中转收料10K PCS/盘;
8. 产品几何中心位置不能设顶出位;
9. 端子接地片共面度在0.05mm以内, 正位度0.02mm以内;
10. 进胶口采用底部细水口进胶;

MIB-008F054

SERIAL NUMBER  
M: PLUG  
F: SOCKET  
NUMBER OF CONTACTS

RECOMENDED STENCIL LAP ERTURE  
(FOR REFERENCE)

X,±	X°,±	UNITS mm	NAME (INTENDED USE)	TITLE: I/M						
.X± 0.05	.X°± 1°	MAT'L	PART NO. (INTENDED USE)							
.XX± 0.02	.XX°± 0.5°	N/A	APPD:	DWG NO: MIB-008F054						
.XXX± 0.015	.XXX°±	FINISH N/A	CHKD:	<table border="1"> <tr> <td>SCALE</td> <td>SHEET</td> <td>REV.</td> </tr> <tr> <td>1:1</td> <td>1/1</td> <td>A</td> </tr> </table>	SCALE	SHEET	REV.	1:1	1/1	A
SCALE	SHEET	REV.								
1:1	1/1	A								
THE GENERATED DRAWING IS BY ACAD, PROE OR IDEAS. DO NOT CHANGE BY HAND.		Q'TY N/A	DR:							